



Teak  
Products



Deck

# Teak

DECK

## Technical data

Product	Strips of bevelled solid wood
Specie	TEAK ( <i>Tectona Grandis</i> )
Adhesive	Not applicable
Length	100mm – 150mm – 200mm
Width	80mm
Thickness	20mm
Density	650kg/m <sup>3</sup>
Surface Finish	Planed, bevelled on its edges
Quality	Standard
Moisture Content	12% +/-2%
Thickness Tolerance	+/-1mm
Width Tolerance	+/-1mm
Width Tolerance	From 0 to +2mm

### Recommendations:

\*Separate the material from the floor (8cm).

\*Store horizontally at room temperature, in a dry place.

\*For outdoor use, it is recommended to use specialized protective products like Lasur made with water-based acrylic resins that leave an open-pored finish, providing adequate protection for the pieces.

\*The products applied should have insecticide and fungicide protection.



La marca del  
manejo forestal  
responsable



Decks continue to prevail as the best choice to customize and harmonize outdoor areas.

The word **Deck** refers to the wood cladding done to a ship's deck, similar to the installation of wood flooring.

It is considered the most practical and functional option for the sense of freshness it gives to spaces that are exposed to the sun, as opposed to stone or tiles that absorb heat and reflect sunlight.

Likewise, for wet areas such as swimming pools, Jacuzzis, showers and saunas, it is the most effective option for allowing water to run through its slots without piling on the surface, providing a hygienic and dry texture.

### Physical Characteristics of the Product

Knots	Admits (healthy)
Pit	Admits (Present in one side)



refocosta\_sas



**refocosta**  
valor natural



[www.refocosta.com](http://www.refocosta.com)